

T. 40 S., R. 2 E., W. M., Oregon.

REHABILITATION OF CORNERS

ground, to bedrock, and in a mound of stone to top, mkd. RS33; from which the original bearing trees

A Shasta fir, dead and down, and badly decayed, bears S.55°W., 15 lks. dist., on which no marks remain.

A Shasta fir, 16 ins. diam., dead and down, and badly decayed, bears N.40°W., 8 lks. dist., with partial scribe marks on decayed face of old blaze.

The original SE. bearing tree, a badly decayed Shasta fir, has been bulldozed out of position, on which the scribe marks T40S R2E S34 BT were found.

And new bearing trees as follows:

A Shasta fir, 6 ins. diam., bears N.60½°E., 48 lks. dist., mkd. T40S R2E S27 RS33 BT.

A Shasta fir, 10 ins. diam., bears S.33½°E., 58 lks. dist., mkd. T40S R2E S34 RS33 BT.

A Shasta fir, 16 ins. diam., bears S.53°W., 10 lks. dist., mkd. T40S R2E S33 RS33 BT.

A Douglas fir, 6 ins. diam., bears N.36½°W., 54 lks. dist., mkd. T40S R2E S28 RS33 BT.

The sec. cor. is located on a ridge, bears N. and S.

I hereby certify that the rehabilitation of corners described in the foregoing field notes in two pages has been executed in conformity with the laws of the United States and the State of Oregon.

Grants Pass, Oregon.
September 21, 1953.

Norman D. Price
Norman D. Price,
Registered Professional
Land Surveyor for Oregon
No. 33.

Present;

Marvin C. Ramsey.
Edwin A. Vail.

REGISTERED
OREGON
LAND SURVEYOR

Norman D. Price

JULY 7, 1944
NORMAN D. PRICE
No. 33



(No map accompanied this Narrative)

T. 40 S., R. 2 E. W. M., Oregon.

REHABILITATION OF CORNERS

The point for cor. of secs. 2, 3, 34, and 35, on S. bdy. of Tp., is determined at the record bearing and distance from the original SE. bearing tree which is the only extant bearing tree.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33; from which the original bearing tree

A Shasta fir, 30 ins. diam., bears S.20°E., 36 lks. dist., with the scribe marks T41S R2E S2 exposed and the BT blaze healed.

And new bearing trees:

A Shasta fir, 8 ins. diam., bears N.72 $\frac{3}{4}$ °E., 64 lks. dist., mkd. T40S R2E S35 RS33 BT.

An incense cedar, 6 ins. diam., bears S.59 $\frac{1}{4}$ °W., 31 lks. dist., mkd. T41S R2E S3 RS33 BT.

A Shasta fir, 6 ins. diam., bears N.40°W., 47 lks. dist., mkd. T40S R2E S34 RS33 BT.

The cor. of secs. 25, 26, 35, and 36 is monumented with the decayed remains of the original wooden stake in a small mound of stone; from which the original bearing trees

A Douglas fir, 46 ins. diam., bears N.34 $\frac{1}{2}$ °E., 67 lks. dist., with blaze healed.

A Douglas fir, 50 ins. diam., bears S.25°E., 29 lks. dist., with blaze healed.

The decayed remains of a Douglas fir, dead and down, bears S.25°W., 83 lks. dist., on which no marks remain.

A Douglas fir, 38 ins. diam., bears N.76 $\frac{3}{4}$ °W., 40 lks. dist., with the scribe marks S26 exposed beneath 98 years overgrowth.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33; from which new bearing trees:

A Shasta fir, 8 ins. diam., bears N.62 $\frac{1}{2}$ °E., 22 lks. dist., mkd. T40S R2E S25 RS33 BT.

A Douglas fir, 11 ins. diam., bears S.66 $\frac{1}{4}$ °W., 21 lks. dist., mkd. T40S R2 E S35 RS33 BT.

The point for cor. of secs. 27, 28, 33, and 34 is determined at the record bearing and distance from the original SW. and NW. bearing trees.

At the corner point,

Set an iron pipe, 3 ft. long, 2 ins. diam., 12 ins. in the

