



	BEARING	DISTANCE
a	N 30° 12' 16\"	104.95
b	N 24° 39' 06\"	111.52
c	N 30° 20' 54\"	267.24
d	N 2° 31' 42\"	32.01
e	N 28° 18' 57\"	52.91
f	N 25° 59' 44\"	52.83
g	N 2° 03' 28\"	52.75
h	N 4° 01' 33\"	204.07
i	N 62° 41' 28\"	134.78
j	N 79° 08' 53\"	100.43
k	N 57° 19' 00\"	289.28
l	N 45° 19' 15\"	150.29
m	N 38° 16' 09\"	155.90
n	N 53° 08' 19\"	57.72
o	N 62° 44' 56\"	74.61
p	N 52° 54' 47\"	68.50
q	N 42° 23' 27\"	59.63
r	N 31° 15' 41\"	77.79
s	N 46° 57' 38\"	150.01
t	N 42° 31' 39\"	141.41
u	N 50° 25' 25\"	104.87
v	N 51° 27' 49\"	38.00



⊙ Fd. Brass Cap Monument per RS. N^o 11540
 Bearings based upon RS. N^o 11540

RECEIVED
 Date 3/29/89
 This Survey Contains
 1 Sheets Map
 APPROVED
 RICHARD TEMPLIN

RICHARD TEMPLIN LAND SURVEYING
 2042 SANDRA PL. 776-0991 MEDFORD, OREGON
PLAT of SURVEY
 of Existing Eagle Point Irrigation Ditch
 LOCATED IN
 SE 1/4 of Section 4, T35S, R1W, WM, Jackson County, Oregon
 SURVEY FOR: EAGLE POINT IRRIGATION DISTRICT MARCH 20, 1989
 EAGLE POINT, OREGON SCALE 1"=200'

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR
 M. J. L.
 RICHARD TEMPLIN

RICHARD G. TEMPLIN
PROFESSIONAL LAND SURVEYOR
2042 Sandra Pl.
Medford, Oregon 97504
(503) 776-0991

SURVEY FOR: Eagle Point Irrigation District
225 Main W.
Eagle Point, Oregon

SURVEY NO. 11549

Location: Section 4, Township 35 South, Range 1 West,
Willamette Meridian, Jackson County, Oregon.

Purpose: To survey the existing center line of the
Eagle Point Irrigation ditch for the purpose
of writing a legal description of said ditch.

Date: March 20, 1989

Basis of
Bearing: Based upon Recorded Survey Number 11540

Procedure: Utilizing a Wild T-16 and Mac 1E EDM,
Tied Southeast corner of Section 4 and East
1/4 Corner of Section 4, then proceeded to tie
in existing ditch center line for legal
description.

