

SURVEY
NO. 12050

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION
TO COMPLY WITH PARAGRAPH 209.130, O.R.S.**

History of original corner establishment:

The original corner point for sections 21, 22, 27, and 28, Township 40 South, Range 2 West, Willamette Meridian, Jackson County, Oregon, was established by Rufus S. Moore under Contract No. 475 dated July 3, 1883. This corner was remonumented from original evidence by the Bureau of Land Management Group 350 (R.Aanrud) in 1975. Surveyor Aanrud set a standard Bureau of Land Management Monument marked:

**BUREAU OF LAND MANAGEMENT
T 40 S R 2 W**

**S21 | S22
S28 | S27**

**1975
CADASTRAL SURVEYS**

Description of corner evidence found:

At the corner point, I found the iron post set by Aanrud in good condition , and the following accessories:

A 41" diameter sawed & burnt fir stump bears N.54°26'W., 7.5 feet distance, with a healed blaze.

A 14" diameter burnt fir bears N.19°27'E., 43.3 feet distance, with a healed blaze.

A 37" diameter sawed & burnt fir stump bears S.61°46'E., 41.9 feet distance to a 5/8" diameter iron pin I drove in the center of the stump.

A 24" diameter sawed & burnt fir stump bears S.77°30'W., 6.4 feet distance to a 5/8" diameter iron pin I drove in the center of the stump.

**Description of accessories I established to perpetuate
the original location of this corner:**

A 13" diameter fir bears N.18°30'W., 95.1 feet distance, scribed T40SR2WS21LS1071 BT.

An 8" diameter fir bears N.58°26'E., 61.0 feet distance, scribed T40SR2WS22LS1071 BT.

NOTE:

A P-K nail in a rock outcrop bears N.77°28'55"W., 396.85 feet distance. This point is the Backsite for the solar observation.

Basis of Bearing
Solar Observation

Date
April 26, 1990

**HAROLD L. CENTER
REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON CERTIFICATE NO. 1071**

**** RECEIVED ****
Date 5-29-90 By SL
This survey consists of:
0 sheet(s) Map
1 page(s) Narrative
**JACKSON COUNTY
SURVEYOR**



SURVEY
NO. 12050

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION
TO COMPLY WITH PARAGRAPH 209.130, O.R.S.**

History of original corner establishment:

The original corner point for sections 21, 22, 27, and 28, Township 40 South, Range 2 West, Willamette Meridian, Jackson County, Oregon, was established by Rufus S. Moore under Contract No. 475 dated July 3, 1883. This corner was remonumented from original evidence by the Bureau of Land Management Group 350 (R.Aanrud) in 1975. Surveyor Aanrud set a standard Bureau of Land Management Monument marked:

**BUREAU OF LAND MANAGEMENT
T 40 S R 2 W**

**S21 | S22
S28 | S27**

**1975
CADASTRAL SURVEYS**

Description of corner evidence found:

At the corner point, I found the iron post set by Aanrud in good condition , and the following accessories:

A 41" diameter sawed & burnt fir stump bears N.54°26'W., 7.5 feet distance, with a healed blaze.

A 14" diameter burnt fir bears N.19°27'E., 43.3 feet distance, with a healed blaze.

A 37" diameter sawed & burnt fir stump bears S.61°46'E., 41.9 feet distance to a 5/8" diameter iron pin I drove in the center of the stump.

A 24" diameter sawed & burnt fir stump bears S.77°30'W., 6.4 feet distance to a 5/8" diameter iron pin I drove in the center of the stump.

**Description of accessories I established to perpetuate
the original location of this corner:**

A 13" diameter fir bears N.18°30'W., 95.1 feet distance, scribed T40SR2WS21LS1071 BT.

An 8" diameter fir bears N.58°26'E., 61.0 feet distance, scribed T40SR2WS22LS1071 BT.

NOTE:

A P-K nail in a rock outcrop bears N.77°28'55"W., 396.85 feet distance. This point is the Backsite for the solar observation.

Basis of Bearing
Solar Observation

Date
April 26, 1990

**HAROLD L. CENTER
REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON CERTIFICATE NO. 1071**

