



**LEGEND.**

- FD. BRASS CAP PER RS 11356
- SET 5/8" X 30" REBAR WITH YELLOW PLASTIC CAP MARKED "TEMPLIN LS2359"
- △ INDICATES CALCULATED POSITION

BEARINGS BASED UPON RS 11356

\*\* NARRATIVE IS SEPARATE DOCUMENT \*\*

33 - 1W - 28 TL ????

**\*\* RECEIVED \*\***  
 Date 8-24-93 By RS  
 This survey Consists of:  
 1. Aerial Map  
 1. Narrative  
 JACKSON COUNTY SURVEYOR

REGISTERED PROFESSIONAL LAND SURVEYOR  
*RT*  
 RICHARD TEMPLIN  
 My Certificate Expires Dec. 31, 1994

**RICHARD TEMPLIN LAND SURVEYING**  
 2042 SANDRA PL. 776-0991 & 474-7720 MEDFORD, OREGON

**MAP OF SURVEY**  
 LOCATED IN  
 S1/2 OF THE SW1/4 OF THE NE1/4 OF SECTION 28,  
 T.38S., R.1W., W.M.  
 JACKSON COUNTY, OREGON

SURVEYED FOR: LINDA McELROY 3484 HWY. 227 TRAIL, OR. 97541  
 DATE: AUGUST 23, 1993

**RICHARD G. TEMPLIN**  
PROFESSIONAL LAND SURVEYOR  
2042 Sandra Pl.  
Medford, Oregon 97504  
(503) 776-0991 • 474-7720

NARRATIVE

SURVEY NO. 13632

SURVEY FOR: Linda Mc Elroy  
3686 Hwy. 227  
Trail, Or. 97541

LOCATION: In the S 1/2 of the SW 1/4 of the NE 1/4 of  
Section 28, Township 33 South, Range 1 West,  
Willamette Meridian, Jackson County, Oregon.

PURPOSE: To monument the NE and NW corners of said S  
1/2 of the SW 1/4 of the NE 1/4 and run true  
line between the two corners.

DATE: August 23, 1993

BASIS OF BEARING: Based upon R.S number 11356.

PROCEDURE: Utilizing previous set control, by the  
U.S.F.S. on Recorded Survey 11356, I computed  
the North line of O.R. 93-12974. Setting the  
NE corner, I ran N 88°58'42" W, 1300.86 feet  
on true line and set the NW corner.

