## ROGUE RIVER -MAP OF SURVEY N89°30'02"W -16.47' OCATED HIGH WATER LINE Located within the Southwest One-quarter and the Southeast One-quarter of Section 19, and within the N88°33'41"W N86°48'21"W 586°41'51"W Northwest One-quarter and the Northeast One-50.02' 38.41 31.05 quarter of Section 30, Township 36 South, Range SAVAGE 4 West of the Willamette Meridian, Jackson CREEK 35°50'00"W 32.81' N83°17'38"W County, Oregon. 27.48 PREPARED FOR: RONALD J. JANECZKO PO Box 5739 FD. 2-1/2" BRASS CAP PER FD. 3" BRASS CAP PER Pahrump, NV 89041 JACKSON COUNTY RE-JACKSON COUNTY RE-ESTABLISHMENT NOTES ESTABLISHMENT NOTES OCTOBER 13, 1990 **№** INST 2006-049107 (0.94 ACRES) T36S R4W 19 20 19 30 30 29 C.S. ELEVATION 1990 FD. 1/2" IRON PIN (ORIGIN UNKNOWN) AT C/L STATION 1071+01.508, SAVAGE-CREEK IES 0.2' NORTHERLY OF SECTION LINE RIGHT-OF-WAY -5.1/4 COR. SEC. 19 S.E. COR. SEC. 19-(SEE DETAIL) (SEE DETAIL) BASIS OF BEARINGS: 589°58'06"E 2665.09' ((589°58'06"E 2665.20')) (588°26'E) 50.00 SOUTH LINE SECTION 19 [50.00'] NORTH LINE SECTION 30 ROGUE RIVER HIGHWAY (HWY. 99) 2515.18 SI7°36'23"E-N74°55'47"E | 51.68 REGISTERED \*\* RECEIVED \*\* 23.23' **PROFESSIONAL** [NT5°46'27"E & 100.00'] SET AT NORTHERLY DATE 5-16-12 BY LAND SURVEYOR **CURVE TABLE** SIDE OF BRIDGE This survey consists of: CURVE DELTA **RADIUS** ARC CHORD BEARING CHORD Carl E. neathann sheet(s) Map 03°12'29" 1667.02 93.34 N76°32'01"E CI 43.33' 582°28'50"W C2 15°06'07" 1637.021 431.481 430.24 \_page(s) Narrative **OREGON C3** 15°06 431.41 JULY 9, 2001 CAEL E. NEATHAMER JACKSON COUNTY C4 15851 N76°41'06"E 50.40 N74°55'47"E SURVEYOR 56545 254.85' 09°08'30" 15851 N80°20'42"E 252.62' Renewal Date 12/31/12 LEGEND: BASIS OF BEARINGS: Indicates a set 5/8-inch diameter by 24 inches long SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250, OREGON REVISED STATUTES iron pin with a plastic cap marked "NEATHAMER SURVEYING". Grid North referenced to the Oregon Coordinate Reference System (OCRS) Grants Pass-Ashland zone, based on the NAD83 (CORS 96) PURPOSE: Pursuant to Client's request and direction, perform a boundary survey, recover controlling monuments, establish (Epoch 2002.000) datum, obtained via GPS methods and the Indicates a set 038 caliber shell casing, lead, tack monuments at boundary corners, and to process and file a Map of Survey in the office of the Jackson County Surveyor. Oregon Real Time GPS Network. Basis applied to the south line of and brass washer marked "NEATHAMER SURVEYING". Section 19, as depicted hereon. Convergence angle to Geodetic PROCEDURE: Utilizing Trimble 5700 GPS equipment with Real-time Kinematic (RTK) methods utilizing the Oregon Real-time North along said line is clockwise 00°04'38". Indicates a found 5/8-inch iron pin with plastic cap marked "D.W. EDWARDS LS 741" per GPS Network (ORGN), a Trimble S6 Robotic Instrument and Trimble TSC2 data collectors with Trimble software, all found monuments were tied in a closed loop traverse or by redundant observations. Records utilized: Instrument Number 2006-OCRS Grants Pass-Ashland zone is a Transverse Mercator Projection 049107 of the Official Records of Jackson County, Oregon; OSHD Drawing Number 8B-2-1 (being Roll Map Number 102/11 in the office of the Jackson County Surveyor), and Surveys Numbered 3430 and 17466 as filed in the office of on the North American Datum of 1983. Published information: Latitude of Origin, 41°45'00" N; Central meridian, 123°20'00" W; False northing, Indicates a found 3/4-inch iron pipe per SN 3430. O meters; False easting, 50,000.000 meters; Central meridian scale the Jackson County Surveyor. is 1.0000043 (exact). Utilizing said GPS equipment, RTK methods and the ORGN, located and tied the North One-quarter corner and the Southeast corner of Section 19, Township 36 South, Range 4 West of the Williamette Meridian, Jackson County, Oregon, establishing the south line of said section and applied basis of bearings (refer to the "BASIS OF BEARINGS" statement hereon). From which, established the centerline and right-of-way per OSHD Drawing Number 8B-2-1 via holding a point that is a 3.50 foot offset northerly from the projected tangent line of the northerly right-of-way (being 50.00 feet westerly along said projected line from centerline station 1071+06.4), and rotating to said measured section line, thereby establishing the location of said northerly right-of-way and the southerly boundary of subject tract of land. Located monuments per Surveys Numbered 3430 and Indicates a brass cap as noted hereon. Indicates a computed position, nothing found or PREPARED BY: Neathamer Surveying, Inc. 3126 State St, Suite 203 Indicates record data per OSHD Dwg 8B-2-1. erly right-of-way and the southerly boundary of subject tract of land. Located monuments per Surveys Numbered 3430 and 17466, the current thread of Savage Creek and the current High Water Line for Rogue River. Utilizing Instrument Number Indicates record data per SN 17466. P.O. Box 1584 Medford, Oregon 97501 Indicates an instrument recorded by number 2006-049107, resolved right-of-way, found monuments and said locations, established the exterior boundaries of the subject Phone (541) 732-2869 pursuant to the Official Records of Jackson tract hereon. County, Oregon. FAX (541) 732-1382 Field work, including establishing the monuments depicted hereon, was completed April 30, 2012. Surveyed acreage hereon Indicates centerline of an existing fence line. differs significantly as compared to the estimated value depicted on the Jackson County Assessors tax lot map due to the north boundary being coincident with the High Water Line, which is subject to change over a period of time. PLOT DATE: May 9, 2012 PROJECT NUMBER: 12012 FNC 0.5'--Indicates the distance to, and which side from the boundary line that the centerline of a Sheet | of | Jackson County Assessor's Map No.: 36 4W 19C, Tax Lot 2900 Drawing N: WSI Projects\Laneczko, Ron\l2O12 Baly Survey 6410 Rogue River Hwy\l2O12\_MO5.pro fence is located.