FILE: RS-33S-02W-01W.DWG

## JACKSON COUNTY MAP OF SURVEY SURVEYOR'S OFFICE LOCATED IN THE LEGEND NE 1/4 OF SECTION 32 CORNER NOTES: ⊗ SET 5/8" X 24" REBAR WITH 1 1/4" YELLOW PLASTIC CAP TOWNSHIP 33 SOUTH, RANGE 1 WEST, WILLAMETTE MERIDIAN (PRIMM LAND SURVEYING, INC. PLS 48490) (141634) (141636) JACKSON COUNTY, OREGON PB REFERENCE BLM GROUP 1592, REFERENCE BLM GROUP 1592, VOLUME OR-RO650, PAGE 441 VOLUME OR-R0650, PAGE 442 O FOUND 5/8" X 24" REBAR WITH 1 1/4" YELLOW PLASTIC CAP EAST 1/16 CORNER COMMON TO SECTIONS 29 AND 32 C3 L1 SECTION 32 (KLEIN & ASSOC. PLS 59002) PER MAP OF SURVEY NO. 21818 FOUND 3-1/4" BLM BRASS CAP FOUND 3-1/4" BLM BRASS CAP DATED 1991 DATED 1991 FOUND MONUMENT AS NOTED BT REFERENCES: BT REFERENCES: 1) FOUND 12" FIR SNAG WITH HEALED FACE 1) FOUND 10" FIR WITH HEALED FACE COMPUTED POINT, NOT MONUMENTED AND TAG DATED 4/91 AND TAG DATED 4/91 S 32° W - 25.4′ N 04° E - 68.2' SECTION CORNER NOT SEARCHED SHOWN FOR REFERENCE ONLY (RECORD 11" FIR - S 32° W, 25.74') (RECORD 8" FIR - N 3° E, 68.3') 2) FOUND 7" OAK WITH HEALED FACE (100000) POINT NUMBER AND TAG DATED 4/91 N 67-3/4° W - 26.15' RM REFERENCE MONUMENT REFERENCE BLM GROUP 1592, (RECORD 6" OAK - N 67-3/4° W, 26.4') This Survey Consists Of: VOLUME OR-RO650, PAGE 440 W.M. WILLAMETTE MERIDIAN \_\_\_\_sheet(s) Map \_\_\_\_page(s) Narrative C2 L1 SECTION 32 {XXX,XX'} GROUND DISTANCE FOUND 3-1/4" BLM BRASS CAP REFERENCE BLM GROUP 1592, DATED 1991 VOLUME OR-RO650, PAGE 438 (XXX.XX') RECORD DISTANCE PER REFERENCED SURVEY BT REFERENCES: JACKSON COUNTY NORTH 1/16 CORNER SECTIONS 32 AND 33 1) FOUND 13" FIR WITH HEALED FACE R1 REFERENCED SURVEY FOUND 2-1/2" BRASS CAP STAMPED LS 1071. DATED 1985 SURVEYOR AND TAG DATED 4/91 ----- PROPOSED ALIGNMENT S 07° E - 42.4' TO NAIL SIDE CENTER BT REFERENCES: (RECORD 9" FIR - S 7° E, 42.24') TEMPORARY CONSTRUCTION EASEMENT 1) FOUND 16" FIR WITH HEALED FACE 2) FOUND 10" OAK WITH HEALED FACE AND TAG DATED 5/85 ---- TEMPORARY WORK AREA AND TAG DATED 4/91 N 76-3/4° E - 29.75' S 69-1/4° W - 32.45' TO NAIL SIDE CENTER LINES PER SURVEY NO. 21814 BEING (RECORD 9" FIR - N 76-3/4° E - 29.7') TL. 1100 ADJUSTED IN THIS SURVEY. (RECORD 9" OAK - S 69-1/4° W, 32.34') 2) FOUND 8" FIR SNAG WITH HEALED FACE S29-T33S-R01W AND TAG DATED 5/85 LEHMAN/CHERYL J ADAMS N $76-1/4^{\circ}$ W - 24.5' (RECORD 6" FIR - N 76-1/4° W, 24.42') \_\_\_\_\_\_\_\_\_\_ REFERENCE BLM GROUP 1592, TL. 700 VOLUME OR-R0650, PAGE 438 S29-T33S-R01W LINE TABLE LINE TABLE C4 L1 SECTION 32 FOUND 3-1/4" BLM BRASS CAP WALTER W NELSON DATED 1991 Line # | Direction | Length Line # | Direction | Length BT REFERENCES: 1) FOUND 8" OAK WITH HEALED FACE L180 | S31°43'52"E | 100.40' L160 S43°17'26"E 18.10' AND TAG DATED 4/91 L181 | S42°01'01"E | 100.40 L161 | S88°17'26"E | 78.50' N 72-3/4° E - 17.5' TL. 1200 (RECORD 7" OAK - N 72-3/4° E, 17.82) S29-T33S-R01W L182 | S36°52'28"E | 86.79' L162 | S36°52'28"E | 225.20' 2) FOUND 8" OAK WITH HEALED FACE AND TAG DATED 4/91 L183 | S36°52'28"E | 3.15' L163 S81°52'28"E 28.28' WALTER W NELSON S 25-1/4° W - 13.4' (RECORD 7" OAK - S 25-1/4° W, 13.53') L184 | S02°46'17"W | 22.70' L164 | S36°52'28"E | 761.44' L185 S88°45'45"E 18.41' L165 | S53°07'32"W | 20.00' L186 N36°52'28"W 2.54' L166 S36°52'28"E 115.45' (1227.40'R1) L167 N24°28'49"E 56.97' {1227.88'} S88'50'39"E 1227.68' L168 | S36°52'28"E | 162.56' LINES 180-186 REFERENCED IN THIS LINE 29 28 \_\_\_\_\_\_ TABLE ARE ADDED PER THIS SURVEY. L169 | S08°07'32"W | 70.71' 537.82' 463.39 LINES 160-169 REFERENCED IN THIS LINE TL. 2000 TABLE ARE PER COUNTY SURVEY NO. 21818. -PROPOSED S32-T33S-R01W CONSTRUCTION EASEMENT SEE DETAIL "B" -PROPOSED ------ALIGNMENT NARRATIVE DETAIL <del>(141636)</del> REGISTERED THE PURPOSE OF THIS SURVEY IS TO SHOW THE MODIFIED PROPOSED CENTERLINE ALIGNMENT AND TEMPORARY CONSTRUCTION **PROFESSIONAL** EASEMENT I, LEONIDES J. SANDOVAL BEING DULY SWORN AS A S88°45'45"E CONSTRUCTION EASEMENT, LOCATED IN SECTION 32, TOWNSHIP 33 SOUTH, RANGE 1 WEST. LAND SURVEYOR PROFESSIONAL LAND SURVEYOR IN THE STATE OF OREGON DO S88°45'45"E 105.15 HEREBY CERTIFY THAT THIS MAP CORRECTLY REPRESENTS A 105.15 SURVEY CONDUCTED UNDER MY DIRECT SUPERVISION IN 90.36 THE CENTERLINE ALIGNMENT AND TEMPORARY **[**{105.17'} CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY CONSTRUCTION EASEMENT BEING MODIFIED BY THIS SURVEY IS SHOWN ON MAP OF SURVEY NO. 21818 ON PAGE 8 OF RECORDING LAW, AS ESTABLISHED BY ORS CHAPTER 209. (105.14'R10) JULY 12, 2016 LEONIDES J. SANDOVAL 58608 NO MONUMENTS WERE SET IN THIS SURVEY. Levels T S. du-THREE NEW MONUMENTS WERE SET IN THIS SURVEY. Expires 6-30-2018 LEONIDES J. SANDOVAL ALL CORNER NOTES ARE PER SURVEY NO. 21818. ALL OF THE OTHER INFORMATION SHOWN ON SAID SURVEY DETAIL "B" NO. 21818 HAS REMAINED UNCHANGED. PORTIONS OF SAID SURVEY NO. 21818 ARE SHOWN HEREIN AS REFERENCE. S36°52'28"E Expires June 3, 2017 DETAIL REFERENCE SURVEYS: 1"=100' SURVEYOR'S CERTIFICATE REGISTERED 1) BLM DEPENDENT SURVEY CS NO. 6404 - APPROVED NOVEMBER 7, 1991 I, KEITH P. PRIMM BEING DULY SWORN AS A PROFESSIONAL LAND **PROFESSIONAL** 2) COUNTY SURVEY NO. 21818 - FILED IN THE JACKSON COUNTY SURVEYORS SURVEYOR IN THE STATE OF OREGON DO HEREBY CERTIFY THAT LAND SURVEYOR OFFICE. DATED OCTOBER 1, 2015 BASIS OF BEARINGS THIS MAP CORRECTLY REPRESENTS A SURVEY CONDUCTED UNDER MY DIRECT SUPERVISION IN CONFORMANCE WITH THE NAD 1983/91 (CONUS) OREGON SOUTH ZONE 3602 GRID NORTH REQUIREMENTS OF THE SURVEY RECORDING LAW, AS ESTABLISHED BY ORS CHAPTER 209, AND HAVE SET THE PROPER NOTE: MONUMENTS AS REFERENCED IN THE LEGEND BY MY OREGON REGISTRATION NUMBER AND SEAL. (BASED ON PREVIOUSLY KEITH P. PRIMM DISTANCES ARE IN US SURVEY FEET. ESTABLISHED PROJECT CONTROL) FURTHERMORE, I APPROVE THE LOCATION OF THE MONUMENTS MEAN MERIDIAN CONVERGENCE ANGLE = $-1^{\circ}36'30''$ Expires 12-31-2018 AS DEPICTED ON THIS SURVEY DRAWING TO BE IN THEIR PROPER (THE CONVERGENCE ANGLE IS COMPUTED BY AVERAGING THE CONVERGENCE ANGLE AT THE NORTH 1/4 OF SECTION 1, TOWNSHIP 33 SOUTH RANGE 2 WEST SCALE FACTOR NOTE AND THE SOUTHEAST CORNER OF SECTION 33, TOWNSHIP 33 SOUTH RANGE 2 WEST) THE DISTANCES SHOWN ON THIS SURVEY ARE GRID KEITH P. PRIMM PLS. 48490 DISTANCES UNLESS NOTED. THE COMBINED SCALE FACTOR = 0.999837519 TO CONVERT FROM GRID TO GROUND MULTIPLY THE DISTANCE BY 1.000162507. PACIFIC CONNECTOR GAS PIPELINE PROJECT WILLAMETTE MERIDIAN JACKSON COUNTY, OREGON PACIFIC CONNECTOR GAS PIPELINE, LP EXAMPLE: 300.00' GRID DISTANCE MAP OF SURVEY SCALE - FEET $300.00' \times 1.000162507 = 300.05'$ GROUND DISTANCE. T.33S., R.1W SECTION 32 Pacific Primm Land Surveying, Inc. TOWNSHIP 33 SOUTH, RANGE 1 WEST, W.M. Connector Klein & Associates, Inc. JACKSON COUNTY, OREGON 1340 NE 4th Street, Hermiston, OR 97838 **GAS PIPELINE** ENGINEERING+SURVEYING+PLANNING LJS DATE: 10-21-2016 ISSUED FOR BID: DRAWN BY: SCALE: 1" = 200' SURVEY PERFORMED FOR: TEL (541) 564-7887 FAX (541) 567-8020 1411 13th Street • Hood River, OR 97031 WILLIAMS PACIFIC CONNECTOR ISSUED FOR CONSTRUCTION: TEL: 541-386-3322 • FAX: 541-386-2515 CHECKED BY: DATE: OCTOBER 21, 2016 PROJECT: 14-02-05 DRAFT: GD, LS

SHEET 1

OF 1

PPROVED BY: