
MAP OF SURVEY

YALE CREEK ROAD JACKSON COUNTY, OREGON

JAIMY WILKINSON

LOCATED IN THE NORTHEAST QUARTER OF SECTION 22 TOWNSHIP 40 SOUTH, RANGE 2 WEST, WILLAMETTE MERIDIAN, JACKSON COUNTY, OREGON



(\$89*38'45"W 330.00' R1) S89°40'31"W 329.54'



Date 11/23/20 By 18 This Survey Consists Of: ___ sheet(s) Map page(s) Narrative JACKSON COUNTY **SURVEYOR**

DATE: 10-16-2020 SCALE: 1"= 120'

LEGEND

 \oplus

BOUNDARY LINE

FOUND 3-1/4" BRASS CAP BUREAU OF LAND MANAGEMENT MONUMENT AS NOTED

FOUND 5/8" IRON PIN PER S/N 4343

FOUND 2-1/2" BRASS CAP PER S/N 8046

SET 5/8" X 24" REBAR WITH YELLOW PLASTIC CAP STAMPED "DROSSOS LS 90718"

SURVEY NUMBER, ON FILE IN THE OFFICE OF THE JACKSON COUNTY SURVEYOR, JACKSON COUNTY, OREGON

S/N

(R1) RECORD DATA PER S/N 4343

(R2) RECORD DATA PER S/N 8046

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

S22 S23

FOUND 3-1/4" BRASS CAP, 0.5'
ABOVE GRADE, PER BUREAU OF
LAND MANAGEMENT
REMONUMENTATION OF CERTAIN
ORIGINAL CORNER POINTS,

APPROVED 08/17/1978

TO SURVEY AND MONUMENT THE BOUNDARY OF THAT TRACT OF LAND DESCRIBED IN INSTRUMENT NUMBER 2020-38612 OF THE OFFICIAL RECORDS OF JACKSON COUNTY, OREGON.

USING A TRIMBLE S-6 ROBOTIC TOTAL STATION AND TRIMBLE R-10 GPS RECEIVERS, I RECOVERED AND TIED EXISTING MONUMENTS OF RECORD AS SHOWN HEREIN. SURVEY NUMBER (S/N) 4343 SURVEYED AND SET THE CORNERS FOR A LARGE MAJORITY OF NEW LOTS LOCATED IN THE NORTH HALF OF SECTION 22. DURING SAID SURVEY, THE NORTH 1/4 CORNER OF SECTION 22 WAS ESTABLISHED. S/N 8046 UNDER CONTRACT WITH THE U.S. FOREST SERVICE, RESURVEYED THE NORTH LINE OF SECTION 22. SAID SURVEY FOUND ALL OF THE CORNERS SET ALONG THE NORTH LINE OF SECTION 22 ON S/N 4343 NORTH OF THE SECTION LINE, AND ALSO ESTABLISH A NEW POSITION FOR THE NORTH 1/4 CORNER. I RECOVERED AND HELD THE 1/4 CORNER SET ON S/N 8046 FOR THE NORTH LINE OF SECTION 22, AND HELD THE CORNERS SET ON S/N 4343 TO ESTABLISH THE SOUTH AND EAST LINE OF THE SUBJECT PROPERTY. THE NORTHWEST CORNER OF THE SUBJECT PROPERTY WAS LOST AND I SET A NEW CORNER ON THE NORTH SECTION LINE AT DEED RECORD BETWEEN THE NEAREST RECOVERED MONUMENT SET ON S/N 4343. I HOLD THE BEARING BETWEEN THE RECOVERED CORNERS ON THE EAST LINE OF THE SUBJECT PROPERTY TO ESTABLISH THE BEARINGS SHOWN FOR THE OTHER CORNERS LYING NORTH OF THE SECTION LINE.

> REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON PHILIP J. DROSSOS

Renewal <u>12-31-21</u>

TERRASURVEY, INC.

PROFESSIONAL LAND SURVEYORS

274 FOURTH STREET ASHLAND, OREGON 97520 (541) 482-6474 terrain@bisp.net

JOB NO. 1377-20

GRAPHIC SCALE 1 INCH = 120 FEET

HEREIN RESULTING IN A BEARING OF N89°45'33"E.

BASIS OF BEARING WAS DETERMINED BY HIGH PRECISION

GPS OBSERVATIONS (NAD83 (2011) EPOCH 2010.00 DATUM) APPLIED TO THE NORTH LINE OF SECTION 22 AS SHOWN