ASSESSOR'S MAP NO. 39 1E 14 BC, TAX LOT 200

## NO. کے P.O.T. 2 1991 اگر LS 759 WITNESS CORNER PER 10166 DATE: 12-14-2023 SCALE: 1"= 30' INST. NO. 88-28127 S89°49'21"E 200.02' (S89°49'55"E 200.00' R1) CLAY STREET INST. NO. 2014-008715 30' Date 1/22/24 By PB S15 + S14 COR This, Survey Consists Of: \_sheet(s) Map page(s) Narrative FOUND 2-1/2" BRASS CAP FLUSH IN CONCRETE JACKSON COUNTY PER S/N 4847 SURVEYOR

## MAP OF SURVEY

760 CLAY STREET ASHLAND, OREGON 97520

> FOR **ELIZABETH CROSS** 760 CLAY STREET ASHLAND, OR 97520

LOCATED IN THE NORTHWEST QUARTER OF SECTION 14, TOWNSHIP 39 SOUTH, RANGE 1 EAST, WILLAMETTE MERIDIAN, CITY OF ASHLAND, JACKSON COUNTY, OREGON

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

<u>PURPOSE:</u>
TO SURVEY AND MONUMENT THE NORTH PROPERTY LINE OF THAT TRACT OF LAND DESCRIBED IN INSTRUMENT NUMBER 2014-008715 OF THE OFFICIAL RECORDS OF JACKSON COUNTY, OREGON.

USING A TRIMBLE S-6 ROBOTIC TOTAL STATION AND TRIMBLE R-10 GPS RECEIVERS, I RECOVERED AND TIED EXISTING MONUMENTS OF RECORD AS SHOWN HEREIN. THE NORTH LINE OF THE SUBJECT PROPERTY WAS ORIGINALLY CREATED AND MONUMENTED ON SURVEY NUMBER (S/N) 10166. I RECOVER AND HOLD THE CORNERS AS SET ON SAID S/N AS SHOWN HEREIN. THE FOUND DISTANCE BETWEEN SAID CORNERS FIT THE RECORD DISTANCE EXTREMELY WELL AND I HOLD SAID RECORD TO ESTABLISH THE NORTHWEST CORNER OF THE SUBJECT PROPERTY.


## LEGEND

BOUNDARY LINE FOUND 2-1/2" BRASS DISK IN CONCRETE FLUSH WITH ASPHALT - AS NOTED FOUND 1.5" BRASS CAP IN CONCRETE 0.2' BELOW GRADE STAMPED "----" PER S/N 12690 FOUND 3" CITY OF ASHLAND BRASS CAP IN MONUMENT CASE STAMPED AS NOTED PER S/N 12690 FOUND 5/8" REBAR WITH BROKEN RED PLASTIC CAP PER S/N 10166 FOUND 5/8" REBAR WITH YELLOW PLASTIC CAP STAMPED "SWAIN LS 759" PER S/N 10166 0 SET 5/8" X 30" REBAR WITH 1-1/2" ALUMINUM CAP STAMPED "DROSSOS LS 90718" INSTRUMENT NUMBER PER JACKSON COUNTY OFFICIAL RECORDS INST. NO. SURVEY NUMBER, ON FILE IN THE OFFICE OF THE JACKSON COUNTY SURVEYOR, JACKSON COUNTY, OREGON RECORD DATA PER S/N 10166 (R1)



Renewal 12-31-25

BASIS OF BEARING WAS DETERMINED BY HIGH PRECISION GPS OBSERVATIONS (NAD83 (2011) EPOCH 2010.00 DATUM) APPLIED TO THE CENTERLINE OF CLAY ST. AS SHOWN HEREIN RESULTING IN A BEARING OF NO0'003'23"W.



## TERRASURVEY, INC.

PROFESSIONAL LAND SURVEYORS

270 FOURTH STREET ASHLAND, OREGON 97520 (541) 482-6474 terrain@bisp.net JOB NO. 1790-23