



RECEIVED
 JACKSON
 AUG - 2 1968
 COUNTY
 SURVEYOR

REGISTERED
 OREGON
 LAND SURVEYOR

MARCH 10, 1944
 L. E. AGER
 21

PLAT OF SURVEY

FOR: R. C. EASTGATE, RT. 1, BOX 'A', JACKSON CREEK ROAD,
 JACKSONVILLE, OREGON.

LOCATION: PORTION S.E. 1/4 OF S.W. 1/4, SEC. 30 & N.E. 1/4 OF NW 1/4, SEC. 31,
 T. 37S., R. 2 W., W.M.

DATE OF SURVEY: JUNE, 1947.

SCALE: 1" = 200'

BEARING DATUM: SEC. LINE ASSUMED E-W.

• = INDICATE 3/4" IRON PIPES SET

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

FOR; R. C. Eastgate, Rt. 1, Box "A", Jackson Creek Road,
Jacksonville, Oregon.

LOCATION: S.E. $\frac{1}{4}$ of S.W. $\frac{1}{4}$ of Section 30 and N.E. $\frac{1}{4}$ of N.W. $\frac{1}{4}$
of Section 31, T. 37 S., R. 2 W., W.M.

PURPOSE: To monument the corners of tracts shown.

PROCEEDURE: Surveyed and monumented the corners of the
tracts shown from points as shown on the
Section line.

A miner commonly known as Whispering Smith
pointed out the Quarter corner and and 1/16 th
corner and also the N.W. corner of Section 31.
He helped a German surveyor in Jacksonville
run this line and also several mining claims.

This survey to be registered at request of
R. C. Eastgate.

I have been unable to find my field notes
showing the bearings and distances to the
two pine trees I scribed for references to
the $\frac{1}{4}$ corner.

