

N.W. COR., SWNW SEC. 31
T. 39S., R. 2E., W.M.

3/4" IRON PIPE
EAST
1321.10

3/4" IRON ROD

SOUTH
3771.41'

SEE REC. SURVEY # 2254

N. 89° 51' W. 678.44'

3/4" IRON ROD

ROAD

3/4" IRON ROD

ACCESS

183.39'

209.76'

STATE

218.50'

1800.0'

3/4" IRON ROD

R/W

5

INTERSTATE

3/4" IRON ROD

3/4" IRON ROD

3/4" IRON ROD

STATE

ACCESS

ROAD

3/4" IRON ROD

3/4" IRON ROD

S. 89° 51' E. 628.0'

N. 5° 16' W. 171.88'

432.41'

CHORD (E = 2465.07)

196.49'

LONG

196.49'

N. 21° 28' 40" W.

N. N.

5. F.

DAVORIAN

RR. XING

N. 87° 25' E. 250.85'

228.34'

N. 60° 45' W. 134.03'

N. 51° 31' W. 127.05'

N. 32° 43' W. 380.0'

S. 47° 40' W. 317.92'

S. 69° 41' W. 383.22'

EASEMENT

N. 14° 24' E. 141.14'

S. 79° 23' E. 197.99'

S. 58° 25' E. 272.16'

SCALE: 1" = 100'

REGISTERED
OREGON
LAND SURVEYOR

MARCH 10, 1944
L. E. AGER
21

SURVEY FOR: DAVID CURTIS,
563 N. MAIN.
ASHLAND, OREGON.

LOCATION: W 1/2 SEC. 31, T. 39S., R. 2E., W.M.

• = MONUMENTS FOUND

○ = 3/4" + 24" IRON PIPES SET FLUSH

BEARINGS SAME AS REC. SURVEY # 2254

DATE: 9-2-67

JACKSON COUNTY
RECEIVED
OCT 10 1967
SURVEYOR

3557

3557

SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250
OREGON REVISED STATUTES

SURVEY FOR: David Curtis, 563 N. Main St., Ashland, Oregon.

LOCATION: West half of Section 31, T. 39 S., R. 2 E., W.M.

PURPOSE : To survey the boundaries of and monument the corners
of parcels of land shown on accompanying map.

PROCEDURE: From the South line of property previously surveyed,
See Rec. Survey # 2254, for North boundary control,
monuments found along the Easterly R/W line of
Interstate 5 for West boundary control and the
S.P. Railroad as control for the Easterly boundary.
I surveyed and monumented the corners of the tracts
shown on accompanying map.

Bearing datum: Same as previous survey No. 2254

