



20' R/W RE TORREN'S NO. 5136

FOUND 2" IRON PIPE
RE: HYDE PARK SUBDIVISION

FOUND 5/8" IRON PIN

FOUND 5/8" IRON PIN

WITNESS CORNER

FOUND 2" GALV. IRON PIPE
S.M. COR. D.L.C. NO. 72

POINT OF TERMINUS
BEING S89°57'55"W
FROM THE S.W. CORNER
OF D.L.C. NO. 72

MAP OF SURVEY
LOCATED IN
S.W. 1/4 OF SEC. 25 & N.W. 1/4 OF SEC. 36, T. 38 S., R. 1 W., W.M.
JACKSON COUNTY OREGON
FOR
EDWARD G. MEILICKE

J. A. HOFFBUHR, REG. L.S., MEDFORD, OREGON
SCALE: 1"=100'
BASIS OF BEARING - R/S NO. 3014
O=SET 5/8" X 24" IRON REINFORCING PIN

REGISTERED
OREGON
LAND SURVEYOR
J. A. Hoffbuhr
NOVEMBER 7 1967
J. A. HOFFBUHR
222

JACKSON COUNTY
RECEIVED
OCT 26 1967
SURVEYOR

3576

3576

Survey Narrative To Comply With Paragraph 209.250
Oregon Revised Statutes

SURVEY FOR: Edward G. Meillicke
320 S. Hilltop Drive
Talent, Oregon

LOCATION: Tract situated in the Southwest One Quarter
(1/4) of Section 25 and the Northwest One
Quarter (1/4) of Section 36, Township 38 South,
Range 1 West, Willamette Meridian, Jackson
County, Oregon.

PURPOSE: To monument the boundaries of the tract of
land indicated on the attached map.

PROCEDURE: The survey control of Recorded Survey No. 3014
was used for this survey along with 2 inch iron pipe on the
boundary of Hyde Park Subdivision. Basis of bearings--Recorded
Survey No. 3014.

October 18, 1967

J. A. Hoffbuhr
Registered Land Surveyor

