



• = SET 5/8" X 30" IRON PINS  
BEARINGS PER RECORDED SURVEY #S-2901



MAP OF SURVEY  
LOCATED IN  
S.W. 1/4 OF S.E. 1/4 OF SECTION 13, T.37S., R.2W., W.M.  
JACKSON COUNTY, OREGON  
FOR  
CITY OF MEDFORD  
C.P. WESTWOOD, P.E. MEDFORD, OREGON  
JANUARY 28, 1969

Survey No. 3983

Survey Narrative to comply with ORS 209-250

Survey For: City of Medford  
City Hall  
Medford, Oregon

Survey Date: January 28, 1969

Survey Location: A portion of the SW 1/4 of the SE 1/4 of Section 13, T37S R2W  
W.M., Jackson County, Oregon

Basis of Bearings: Per recorded Survey #2901

Survey Procedure:

The monuments found for control of this survey are as follows: A 1" axle with gear being the N.W. corner of Vol. 67, Page 500, a 3/4" iron pipe being the N.E. corner Vol. 360, Page 243, a 3/4" iron pipe being the N.W. corner Lot 10, Block 2 of Crew's Subdivision and a 4" brass disc being the N.W. corner of D.L.C. 61, T37S R2W W.M. For the centerline of Table Rock Road I used the pipe in monument case at the intersection of the W/L of Table Rock Road and the northerly line of U.S. 99 Highway, and a copper pin set in concrete pavement at the P.T. of the centerline curve of Merriman Road southerly of DeBarr Avenue, per city field book #280.

The north line of this survey was set from the found axle, N80° 59' 00" E on a prorated bearing from this survey along the northerly line of Vol. 67, Page 500 to intersect the west line of Vol. 265, Page 221. Therefore, the east line was determined from the aforesaid volume and page.

The other corners were set as shown on the accompanying plat as requested by the client.

Respectfully Submitted:

*C. P. Westwood*

March 3, 1969

