N89°45'55"W

4581

<u> 30</u>

32

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209-250

Survey for:

Mr. Larry Rich

71-11

Rt. 2, Box 491 Gold Hill, Ore.

Survey by:

Edward A. McGinty, R.S.

Medford, Oregon

May 1971

Basis of Bearing:

Survey No. 3099.

Location of Survey:

SE. 1/4 of Section 30,

T35S, R2W., WM.

Precedence of Survey:

SE. corner of Section 30, found a sand stone broken during excavation, with apparent chisel marks, approx. 10ihs. deep. Remaining portion of stone approx. 4" x 6" x 2^{1}_{2} ". Set a 3/4 in. iron pin, 24 ins. long, 4 ins. deep. Found 3 remaining BT's, NE SW and NW agreeing for bearing and distance, also found a 5/8 in. iron pin, N.60°15'W., 0.81 ft.

E-W fence bears southerly, 30 ft.

NE corner of Section 30, found stone apparently leaning northerly, approx. 18 ins. deep.

Surveyed tract of land as shown, set $5/8 \times 24$ in. iron pins, approx. flush with the surface.

Deed calls to the tracts lying southerly, apparently the intent was to be parallel with the section line.

Tracts lying northerly, the pparent intent was to be parallel to the 1/16 line.

From previous data acquired on survey 1965 on the West line with Co. data on the south line and this survey computed theo E-W center line and E-W 1/16 line.

remarks - the E.1/4 cor. falls approx. 0.53 north and 0.15 west of possible corner set by Ager.



