



End stone with + 6x8x14 pipe beneath - & bearing trees in evidence

1/4 CORNER SECTIONS 26 & 35  
 End 24" oak S87°W 206.58 reverse of 48'S  
 22 oak N21°W 295.02 no mark or fare  
 set 5/8" pin in mound of stones in fence line  
 mkd 10' oak S38°E 26.62 1/4 S 35 BT

(West 39.93 chs)  
 N 89°25'04"W  
 26.4892

PROPORTIONED CORNER  
 set 5/8" pin in edge of pond in mound of stones  
 E-W fence 28' South  
 Dam top 70' West

N 1/16 SECTIONS 34 & 35  
 set 5/8" pin in mound of stone  
 mkd 14" oak S75°E 25.5 N 1/16 S35 BT  
 14 oak S17°W 31.8 N 1/16 S34 BT

1/4 CORNER SECTIONS 34 & 35  
 End remains 20" oak stub N46°W 19.8 reverse of BT  
 30" pine stub S83°E 31.68 no marks rotten  
 set 5/8" pin 30" long in mound of stones  
 mkd new 5" Madrone N60°E 38.1 1/4 S 35 BT  
 20" 8 oak S24°W 62.2 1/4 S 34 BT

REGISTERED PROFESSIONAL LAND SURVEYOR  
*William A. Eimstad*  
 OREGON  
 MAY 4, 1964  
 WILLIAM A. EIMSTAD  
 371

JACKSON COUNTY  
 RECEIVED  
 JUN 8 1973  
 SURVEYOR

SURVEY FOR OLIVER A. GUSTAFSON  
 SECTION 34 T35S, R2W, W.M.  
 EIMSTAD & ASSOCIATES  
 1717 WASHINGTON ST EUGENE  
 MAY 1973  
 SCALE  
 1 INCH = 400 FEET