

R/S NO. 6384

SECTION CORNER  
FD. 1 1/4" IRON PIPE  
PER R/S NO 6384

FALLS 1.0' NORTH  
OF FENCELINE NB

N89° 54' 30" E

FALLS 2.5' NORTH  
OF FENCELINE

1/4 SECTION CORNER  
FD. BRASS DISK MONUMENT  
PER COUNTY RE-ESTAB

500°05'30" E  
 1504.66'  
 887.04'  
 887.04'  
 887.04'  
 500°12'18"E  
 1502.61'  
 MEAS. 500°16'04"E 1338.55'  
 (REC 500°16'30"E 1338.04')  
 124.02'  
 Δ=36°32'24"  
 R=288.310  
 L=158.71'  
 737.84  
 ROAD  
 589°45.00"W  
 888.53'  
 5.00'  
 888.54'  
 7.86'  
 500°08'54"E  
 1505.07'  
 25.00' PRIVATE WAY  
 PER J.C. INST. NO. 78-09858  
 FD. 5/8" IRON PIN  
 PER R/S NO. 6384

- NORTH R/W LINE OF LINN ROAD WAS  
DETERMINED AS BEING 30.0' NORTH  
OF THE AVERAGE EXISTING CENTERLINE  
AS MEASURED ON NOVEMBER 15, 1977

MAP OF SURVEY  
LOCATED IN  
N.W. 1/4 of Sec. 04, T36S, R1W, W.M.  
JACKSON COUNTY, OREGON  
FOR


**RUTH KNEASS**

HOFFBUHR SURVEYING, INC. MEDFORD, OREGON

SCALE: 1"=400'      DECEMBER 27, 1977

BASIS OF BEARING R/S NO.3080

Ø = SET 5/8" x 24" IRON PIN


 CENTER OF SECTION 4  
 FD 3/4" IRON PIPE  
 PER R/S NO. 3080

1/4 SECTION CORNER  
FD. BRASS DISK MONUMENT  
PER COUNTY RE-ESTAB

RECEIVED  
JAN 11 1978  
SURVEYOR

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

Richard L. Bath

JUL 30 1974  
 RICHARD L. BATH  
 N. 1069

**7065**

S4 36 1W (T.L 601.

SURVEY NO. **7065**

SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250  
OREGON REVISED STATUTES

SURVEY FOR: Ruth Kneass  
10525 Agate Road  
Eagle Point, Oregon 97524


LOCATION: Northwest one-quarter (1/4) of Section 4,  
Township 36 South, Range 1 West, Willamette  
Meridian, Jackson County, Oregon

PURPOSE: To survey, monument, and redescribe by metes and  
bounds the three subject tracts as described in  
Jackson County Instrument No. 71-16328

PROCEDURE: Utilizing control established or found per Recorded  
survey No. 3080 and 6384, located and tied monuments as shown on  
the attached map. The Northwest one-quarter (1/4) of Section 4  
was coordinated and bearings on the two North-South interior lot  
lines were determined by inverse method between equal thirds on  
the North line and South line of said quarter section. Road con-  
trol was continued from that established on the East by Recorded  
Survey No. 3080 and on the West by Recorded Survey No. 6384. Monu-  
ments were set as shown.

Basis of bearing--Recorded Survey No. 3080

January 5, 1978



Richard L. Bath  
Hoffbuhr Surveying, Inc.