Set 5/8 x 30 inch Iron Pin tagged RLS 759

Set 5/8 x 30 inch Iron Pin w/Alum. Cap mkd. CSN 1/64

588039 IE

7225

<u>ត្រីយល់ ប្រជាពេក គ្រង ប្រជាពិធី ដែលប្រជាពិធី ប្រជាពិធី ប្រជាពិធី</u> ... 10 \_\_ SCALE

## SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250 OREGON REVISED STATUTES

SURVEY FOR: Harold Gentry

70 Hillendale

Ashland, Oregon 97520

LOCATION:

Situated in the North half of Section 8, Township 39 South, Range 1 East of the Willamette Base and Meridian, Jackson

County, Oregon.

PURPOSE:

To survey the parcel of land as shown on the accompanying map and prepare legal descriptions for boundary line agreements on the

Easterly and Westerly boundaries, as shown.

PROCEDURE:

From previously established control, proceeded to run control to the areas where the corners were to be set. Tied fences and fence corners to obtain the relationship of lines of occupation in relation to the interior sections lines as determined by subdividing Section 8. The North boundary line was established along the average location of the existing Fast-West fence which is situated a few feet southerly of the true Deed Record boundary line, which would be the North boundary line of the Southeast quarter of the Northwest quarter of Section.8.

The remainder of the survey was conducted as shown on the accompanying

REGISTERED PROFESSIONAL Everett L. Swain Professional Land Surveyor Ashland, Oregon 97520

RECEIVED MAY 0.2 1978 SURVEYOR