

CERTIFIED RECORD OF CORNER PERPETUATION

This corner was set by Hans W. Thielsen on a proportionate basis in 1955.

T325, RIW, W.M.
14 $\frac{15}{22}$

I find a 1 inch outside diameter pipe with a brass cap attached, from which the one remaining bearing tree, a

White Fir 24" diam. bears record S 39 $\frac{1}{4}$ °E 20.5 ft.

I perpetuate the corner position by taking the following new tree and place a brass washer bearing my registration no. in the lower blaze:

A D. Fir 8" diam. marked $\frac{1}{4}$ S BT bears N 41°E. 70.1 Ft.

Va. = 15 3/4°

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Kurt C. Weaver
OREGON
JULY 14, 1978
KURT C. WEAVER
1679

I hereby certify the above corner perpetuated as herein described on November 17, 1978.

Witnesses :

Herb Farber
Reg Harding

Office of Surveyor County of Jackson,
State of Oregon, I hereby certify that the within
instrument was filed in this office for record on
7TH day of DEC., 1978.

Edward A. McEnty by *James B. Brown*
County Surveyor Deputy

JACKSON COUNTY
RECEIVED
DEC 7 1978
SURVEYOR