

7633

Vol. 236 P. 368
d.r. j.c.o.

Section line

S. 89°43'23"E.

247.24'

1/4 Sec. Cor.
Fd. 2" Pipe

R/W

15'

WESTWOOD STREET

R.S. No. 6348

S. 00°27'03"E.
496.505'

S. 00°13'53"E.
1,333.07'

Fd. 1" G.I. Pipe
w/welded top
replaced w/5/8" I.
Pin tagged RLS 759

SE cor. C.B. French
tract V. 61 P. 132
d.r. j.c.o.

N. 89°55'55"W.
49.50'

S. 00°41'17"E.
833.705'

BOUNDARY LINE
AGREEMENT

Doc. No. 78-11551
o.r. j.c.o.

N. 16°26'26"W.
547.11'

BOUNDARY LINE
AGREEMENT

Doc. No. 78-07062
o.r. j.c.o.

MAP OF SURVEY

located in
N 1/2 of Sec. 8, Twp. 39S., R. 1 E.W.M.
Jackson County Oregon

for

WILLIAM H. KNEEBONE, JR.

EVERETT L. SWAIN, R.P.L.S.

ASHLAND, OREGON

Scale: 1"=100'
Basis of Bearing:

June 1, 1978
N.O.A.A. True Bearing N-S $\frac{1}{4}$ Sec. 8

- Found monument as shown
- Set 5/8 x 30 inch Iron Pin tagged RLS 759

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Everett L. Swain

OREGON
JULY 8, 1966
EVERETT L. SWAIN
759

JACKSON COUNTY
RECEIVED
FEB 28 1979
SURVEYOR

(100) 58 BA 391E

7633

7633

SURVEY NO. _____

SURVEY NARRATIVE TO COMPLY WITH PARAGRAPH 209.250
OREGON REVISED STATUTES

SURVEY FOR: William H. Kneebone, Jr.
494 Orchard Street
Ashland, Oregon 97520

LOCATION: Situated in the North half of Section 8, Township 39 South, Range 1
East of the Willamette Base and Meridian, Jackson County, Oregon.

PURPOSE: To establish boundary lines as shown hereon to be cleared by
boundary line agreements.

PROCEDURE: From previous control established by this office proceeded to survey
and monument said boundary lines as shown on the accompanying map.

Everett L. Swain
Professional Land Surveyor
Ashland, Oregon

