

N 89°43'17" W

1141.42'

Fd. 5/8" I.P.

N 3°42'10"E  
28.26'

N 27°26'30"E  
80.47'

N 12°42'45"E  
50.88'

N 16°46'55"W  
50.88'

(S.N. 6490)

N 31°30'40"W  
86.24'

N 89°43'10"W  
183.41'

599.05'

N 08°03'27"E  
338.27'

528.81'

1324.60'

S 0°03'30"E

S 39°03'50"E  
388.40'

500.00'

S 71°30'38"E  
402.29'

S 86°49'13"E  
70.72'

N 27°39'39"E  
85.83'

N 45°28'59"E  
195.29'

N 76°41'20"E  
562.06'

N 77°59'23"E  
556.33'

22.00'

S 0°09'30"E

A SURVEY IN  
SE 1/4 SEC 20 T.34S R.1 W W.M.

FOR  
BILL LITTLEFIELD  
(73-38-4)

BY EDWARD A. MCGINTY  
MEDFORD, OREGON  
FEBRUARY, 1979

SCALE 1" = 100'  
O = 5/8" x 24" I.PIN

Δ = 56°56'44"  
R = 60.00'  
L = 59.63'

Δ = 56°13'32"  
R = 70.00'  
L = 68.69'

S 29°17'02"E  
21.11'

N 68°09'E  
90.82'

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 10, 1953  
EDWARD A. MCGINTY  
301

JACKSON COUNTY  
RECEIVED  
JUN 26 1979  
SURVEYOR

2882

Fd. 5/8" I.P.

1/4 Cor.

(73-38)

7887

T34 R1W, Sec 20 (TL 2600)



1831

SURVEY NO. 7887

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209-250

Survey for: Mr. Bill Littæefield 78-38  
P.O. Box 281  
Shady Cove, Or 97534

Survey by: Edward A. McGinty  
Medford, Or  
Feb. 1979

Basis of Bearing: Survey No. 7565

Location of Survey: SW 1/4 of the SE 1/4 of Sec. 20  
T34S, R1W

Precedence of Survey:

Portions of previous surveys 6490, 7564 and 7565 were used for clients convenience and are not retracements.

The westely line was determined by running southerly on line with the South 1/4 cor. of Sec. 20; thence traversing south-easterly to intersect at an iron pin on the Westerly line of previously shown on survey No. 7564.

There is proposed r/w reserving a 60 ft. strip of the most easterly line of the larger tract for road purposes.

The smaller tract shown is a proposed change of tract boundaries as was shown on previous survey No. 7564.

Iron pins set being 5/8 in. x 24 in. and set approx. flush with the surface.

