

2688

JACKSON COUNTY
RECEIVED
JUN 9 1980
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Robert Mason

OREGON
JULY 22, 1974
ROBERT MASON
1011

8397

(14004 14500) 36 3W 25'

SURVEY NARRATIVE

8397

SURVEY in the West Half of Section 25, Township 36 South, Range 3 West of the Willamette Meridian, Jackson County, Oregon.

SURVEY FOR: Earl Millhouse
6029 Foley Lane
Central Point, Ore.

F. Dougherty
6039 Foley Lane
Central Point, Ore.

SURVEY BY: Robert Mason
415 Surrey Dr.
Grants Pass, Ore.

PURPOSE OF SURVEY: To mark the lines and corners of North Half of NE $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$ and the South Half of SE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 25.

PROCEDURE: I first locate the N $\frac{1}{4}$ corner, which is marked with a 5/8" iron rod. There are no accessories so I measure to the NW corner of the section. I do not find the corner but find two Brass Cap Monuments, which are referenced to the corner. I calculate the position of the corner and check against record measurements. I then scribe two bearing trees for future reference. I then measure southerly to the S $\frac{1}{4}$ corner. Then from near the midpoint of this line, I traverse to the W $\frac{1}{4}$ corner and to the E $\frac{1}{4}$ corners. I then calculate the location of the center of the section and mark it with a 1 $\frac{1}{2}$ inch iron pipe.



I did not measure the west line of the NW $\frac{1}{4}$. The dimension shown is calculated from the measurement of the other three sides. I then computed the location of the NW corner of the South Half of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$, and set 5/8" iron rods to mark the corners as shown on the plat.

To set the SW corner of the North Half of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$ would require measuring the south and west lines of the SW $\frac{1}{4}$. I set this as a witness corner only, it's location being at the point of intersection of a line parallel to the north line of the SW $\frac{1}{4}$ and 331.50 feet south, and a line 658.96 feet west of and parallel to the east line of the SW $\frac{1}{4}$.


Accessories to the corners are shown on the plat. I did find a discrepancy in notes acquired from the County Surveyor's Office. Said notes call for a 4" W. Oak CS BT which bears N 33 $\frac{1}{2}$ $^{\circ}$ W, 25.9 ft. I found a 5" W. Oak N 33 $\frac{1}{2}$ $^{\circ}$ E, 25.9 ft. This tree also scribed. Reference being to the W $\frac{1}{4}$ corner Sec. 25.

SURVEY executed with Lietz Theodolite and EDM.

SURVEY completed May 20, 1980.



Robert Mason



(TH 9200) 39 1W 30