

Sec. Cor. Secs. 26, 27, 34 & 35
Fed. JCS BC, 1978

27|26
34|35

T. 39S.

9732

- FOUND CORNER
- CORNER SET THIS SURVEY
- LINE RUN THIS SURVEY
- () GLO BEARING & DISTANCE

Note: Distances from BTs are from
nails in lower face.

Basis of bearing, Solar Observation.

W 1/4 Cor. Sec. 35
Set by prop. a 2 1/2" BC
in a stone mound.
BTs:
6" PP, S67°W, 3.56'
6" Ced., N 31°E, 7.98'

T39S R4E
1/4
S 34 | S 35
1983
ORLS 1139

NOTE: This corner was searched for by,
G. M. Uppington, Weyerhaeuser, 1933
BLM, Cedestral, 1966
Jackson County Surveyor, 1975

(South)
S 00° 28' 28" E

2651.609'
(40.00ch.)

R. 4E.

2651.609'
(40.00ch.)

SC btwn. Secs. 34 & 35
Fed. JCS BC, 1974

34|35

** RECEIVED **
Date 9/19/83 By K
This survey consists of:
1 sketch map
0 page narrative
JACKSON COUNTY
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Dennis L. Brandt
OREGON
SEPT. 23 1977
DENNIS L. BRANDT
1989

MAP OF SURVEY IN
SEC. 35, T. 39S., R. 4E., W.M.
JACKSON COUNTY, OREGON



Weyerhaeuser Company
EASTERN OREGON REGION

SCALE: 1" = 600'
SURVEY: Gallagher

DATE: AUG. 1983
DEL.: Cook

9732